

## PvBlack X50/X50B

### 特种炭黑 Special carbon black

#### 简介 introduction:

特种炭黑 PvBlack X50/X50B 设计用于通用母粒、水、油性色浆、粉体涂料、电泳涂料等。对以上提供中等黑度、偏蓝相，高光泽，高流动性。Special carbon black PvBlack X50/X50B is designed for general purpose masterbatch, water, oil paste, powder coating, electrophoretic coating, etc. The above provides medium blackness, bluish phase, high gloss, high fluidity.

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	粉末 Powder
平均原生粒径 Average original particle size (nm)	20±1
BET 比表面积 BET Specific surface area (m <sup>2</sup> /g)	200±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	55±5
相对着色, IRB#3(%) Tinting Strength	125±5
挥发份 Volatile matter (%)	1.0±1
PH 值	8.5±0.5

#### 应用与特性 Application and characteristics:

- ◆ 中等黑度 Medium blackness
- ◆ 蓝相 blue phase
- ◆ 高光泽 High gloss
- ◆ 高流动性 High fluidity

#### 推荐应用 Recommended application:

用于通用母粒、水/油性色浆、粉体涂料、电泳涂料

For general purpose masterbatch, water, oil paste, powder coating, electrophoretic coating.

包装 packing: 10KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS:The Data above is provided in good faith,FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号

电话: +86 (0) 755 23246611; 13510821649

传真: +86 (0) 755 29467129

邮箱: texong@163.com 网址: www.texong.com